

CH4VRS

DM11VRS(OT) - DM11VRS(IT)

CM11VRS(OT) - CM11VRS(IT)

DM12VRS(OT) - DM12VRS(IT)

DP11VRS

CH4VRS

The Macdonald CH4VRS is a lightweight vibration reduced chipping hammer.

	CHU	CK SIZE	WE	IGHT	LENG	этн	вог	RE	STR	OKE	FRQ'	CY	AIR	CONS	REC.W	RKG	AIR HOSE	
model	ins	mm	lbs	kg	ins	mm	ins	mm	ins	mm	bpm	hz	cfm	L/sec	psi	bar	ins	
CH4VRS	5/8.	16Hex	14.3	6.5	16	400	1.25	32	1.5	38	3400	57	22	10	90	6	1/2.	



DM11VRS(inside trigger)

This Macdonald Vibration Reduced Demo pick is ideal for demolition work in brick and concrete. The DM11VRS hosts versatility and low vibration levels combined in a single tool with Quick Change Retainer and 4 Bolt Backhead for incressed durability.

	сниск	SIZE	WEI	GHT	LENG	тн	ВО	RE	STR	OKE	FRQ'	CY	AIR C	CONS	REC.WI	RKG	AIR HO	OSE	HOSE FITTING
model	ins	mm	lbs	kg	ins	mm	ins	mm	ins	mm	bpm	hz	cfm	L/sec	psi	bar	ins	mm	
DM11VRS	(hex)7/8.x3.1/4.	22 x 82.5	28.6	15	21.6	550	1.57	40	3.5	89	1620	27	40	18.5	90	6	3/4.	19	3/4. BSP

Notes: 1. The weights shown include a silencer 2. The weights of the bare tools are 3.4lbs (1.5kg) lighter



DM11VRS(outside trigger)

This Macdonald Vibration Reduced Demo pick is ideal for demolition work in brick and concrete. The DM11VRS hosts versatility and low vibration levels combined in a single tool with Quick Change Retainer and 4 Bolt Backhead for incresed durability.

	CHUC	K SIZE	WEI	GHT	LEN	ЭТН	во	RE	STR	OKE	FRQ'	CY	AIR	CONS	REC.W	rkg	AIR H	IOSE	HOSE FITTING	
model	ins	mm	lbs	kg	ins	mm	ins	mm	ins	mm	bpm	hz	cfm	L/sec	psi	bar	ins	mm		
DM11VRS(h	ex)7/8.x3.1/	4. 22 x 82.5	28.6	13.5	21.6	550	1.57	40	3.5	89	1620	27	40	18.5	90	6	3/4.	19	3/4. BSP	_





CM11VRS(inside trigger)

This Macdonald Vibration Reduced Tunnelling Pick is ideal for working in confined environments, fitted with a screwed retainer it gives low vibration levels in conjunction with maximum manouverability.

	CHUCK :	SIZE	WEI	GHT	LENG	тн	ВОІ	RE	STR	OKE	FRQ'	CY	AIR C	CONS	REC.W	RKG	AIR H	OSE	HOSE FITTING
model	ins	mm	lbs	kg	ins	mm	ins	mm	ins	mm	bpm	hz	cfm	L/sec	psi	bar	ins	mm	
CM11VRS	3/4.x 3.1/4.	19 x 82.5	27	12.3	21.6	550	1.57	40	3.5	89	1620	27	40	18.5	90	6	3/4.	19	3/4. BSP

Notes: 1. The weights shown include a silencer 2. The weights of the bare tools are 3.4lbs (1.5kg) lighter



CM11VRS(outside trigger)

This Macdonald Vibration Reduced Tunnelling Pick is ideal for working in confined environments, fitted with a screwed retainer it gives low vibration levels in conjunction with maximum manouverability.

	CHU	CK SIZE	W	EIGHT	LEN	GТН	во	RE	STR	OKE	FRQ'	CY	AIR	CONS	REC.WR	KG	AIR H	OSE	HOSE FITTING
model	ins	mm	lbs	kg	ins	mm	ins	mm	ins	mm	bpm	hz	cfm	L/sec	psi	bar	ins	mm	
CM11VRS	3/4.x 3.1/4.	19 x 82.5	27	12.3	21.6	550	1.57	40	3.5	89	1620	27	40	18.5	90	6	3/4.	19	1/2. BSP





DM12VRS(inside trigger)

This Macdonald Vibration Reduced Demo pick is ideal for demolition work in brick, concrete and pile capping. The DM12VRS hosts versatility and low vibration levels combined in a single tool with screw Retainer and 4 Bolt Backhead for incressed durability.

	CHUCK S	IZE	WEIG	ЭНТ	LENGT	гн	воі	RE	STRO	OKE	FRQ'	CY	AIR C	ONS	REC.WF	RKG	AIR HO	SE	HOSE FITTING
model	ins	mm	lbs	kg	ins	mm	ins	mm	ins	mm	bpm	hz	cfm	L/sec	psi	bar	ins	mm	
DM12VRS	63/64.x2.15/16.	25 x 75	36.3	16.5	28.76	730.5	1.4	36	7.5	191	980	16	42	20	90	6	3/4.	19	1/2. BSP

Notes: 1. The weights shown include a silencer 2. The weights of the bare tools are 3.4lbs (1.5kg) lighter



DM12VRS(outside trigger)

This Macdonald Vibration Reduced Demo pick is ideal for demolition work in brick, concrete and pile capping. The DM12VRS hosts versatility and low vibration levels combined in a single tool with screw Retainer and 4 Bolt Backhead for incressed durability.

	CHUCK SIZE	WE	IGHT	LENG	гн	во	RE	STR	OKE	FRQ'	CY	AIR C	CONS	REC.WF	RKG	AIR H	OSE	HOSE FITTING
model	ins mm	lbs	kg	ins	mm	ins	mm	ins	mm	bpm	hz	cfm	L/sec	psi	bar	ins	mm	
DM12VRS	63/64.x2.15/16. 25 >	75 36.3	3 16.5	28.76	730.5	1.4	36	7.5	191	980	16	42	20	90	6	3/4.	19	1/2.BSP





DP11VRS

This Macdonald Vibration Reduced Demo pick is ideal for demolition work in brick, concrete and pile capping. The DP11VRS hosts versatility and low vibration levels combined in a single tool with Quick Latch Retainer and 4 Bolt Backhead for incressed durability.

	сниск	SIZE	WE	IGHT	LENG	этн	ВО	RE	STR	OKE	FRQ'	CY	AIR	CONS	REC.V	VRKG	AIR I	HOSE	HOSE FITTING
model	ins	mm	lbs	kg	ins	mm	ins	mm	ins	mm	bpm	hz	cfm	L/sec	psi	bar	ins	mm	
DP11VRS	(hex)7/8.x3.1/4.	22 x 82.5	28	12.7	21	533	1.38	35	4.3	110	2040	37	35	16.2	90	6	1/2	12.7	3/4. BSP



VR DEMOTOOLS COMPARISON SHEET

	СНИС	K SIZE	WI	IGHT	LEN	GTH	ВС	RE	STF	ROKE	FRO	Q'CY	AIR	CONS	REC.W	/RKG	AIR H	IOSE	
model	ins	mm	lbs	kg	ins	mm	ins	mm	ins	mm	bpm	hz	cfm	L/sec	psi	bar		ins	
CH4VRS	5/8.	16Hex	14.5	6.5	16	400	1.25	32	1.5	38	3400	57	22	10	90	6		1/2.	
	СНИС	K SIZE	WI	EIGHT	LEN	GTH	ВС	RE	STI	ROKE	FRO	Q'CY	AIR	CONS	REC.	WRKG	AIR	HOSE	HOSE FITTING
model	ins	mm	lbs	kg	ins	mm	ins	mm	ins	mm	bpm	hz	cfm	L/sec	psi	bar	ins	mm	
DP11VRS	(hex)7/8.x3.1/	4. 22 x 82.5	28	12.7	21	533	1.38	35	4.3	110	2040	37	35	16.2	90	6	1/2	12.7	3/4. BSP
	CHUC	K SIZE	WE	IGHT	LEN	GTH	ВС	RE	STF	OKE	FRO	Q'CY	AIR	CONS	REC.W	/RKG	AIR H	IOSE	HOSE FITTING
model	ins	mm	lbs	kg	ins	mm	ins	mm	ins	mm	bpm	hz	cfm	L/sec	psi	bar	ins	mm	
DM11VRS	(hex)7/8.x3.1	/4. 22 x 82.5	28.6	5 13.	5 21.6	550	1.57	40	3.5	89	1620	27	40	18.5	90	6	3/4.	19	1/2. BSP
Notes:1. Th	e weights sh	own inclu	de a sil	encer	2. The w	eights o	f the bare	tools a	re 3.4lbs (1.5kg)	ighter.								
	СНИС	K SIZE	WI	IGHT	LEN	GTH	вс	RE	STF	ROKE	FRO	Q'CY	AIR	CONS	REC.W	rkg	AIR H	OSE	HOSE FITTING
model	ins	mm	lbs	kg	ins	mm	ins	mm	ins	mm	bpm	hz	cfm		psi	bar	ins	mm	
	(hex)7/8.x3.1/4			13.5		5 550	1.57		3.5	89	1620	27	40	18.5	90	6	3/4.	19	1/2. BSP
Notes: 1. In	e weights sh	iown inciu	de a sii	encer	2. The w	eignts o	t the bare	toois a	re 3.4lbs (1.5кд) і	ignter.								
	CHUC	K SIZE	WI	IGHT	LEN	GTH	ВС	RE	STI	ROKE	FRO	Q'CY	AIR	CONS	REC.W	/RKG	AIR H	IOSE	HOSE FITTING
model	ins	mm	lbs	kg	ins	mm	ins	mm	ins	mm	bpm	hz	cfm	L/sec	psi	bar	ins	mm	
CM11VRS	3/4.x 3.1/4.		27	12.3	21.6	550	1.57	40	3.5	89	1620	27	40	18.5	90	6	3/4.	19	1/2. BSP
Notes: I. In	e weights sh	iown inciu	de a sii	encer	2. The w	eignts o	t the bare	toois a	re 3.4lbs (1.5кд) і	ignter.								
	CHUC	K SIZE	WI	IGHT	LEN	GTH	ВС	RE	STF	ROKE	FRO	Q'CY	AIR	CONS	REC.W	rkg	AIR H	OSE	HOSE FITTING
model	ins	mm	lbs	kg	ins	mm	ins	mm	ins	mm	bpm	hz	cfm	L/sec	psi	bar	ins	mm	
CM11VRS	3/4.x 3.1/4.		27	12.3	21.6	550	1.57	40	3.5	89	1620	27	40	18.5	90	6	3/4.	19	1/2.BSP
Notes:1. Th	ne weights sl	hown inclu	ıde a si	lencer	2. The w	eights o	f the bare	tools a	re 3.4lbs (1.5kg)	ighter.								
	СНИС	K SIZE	W	IGHT	LEN	GTH	ВС	RE	STF	OKE	FRO	Q'CY	AIR	CONS	REC.W	RKG	AIR H	OSE	HOSE FITTING
model	ins	mm	lbs	kg	ins	mm	ins	mm	ins	mm	bpm	hz	cfm	L/sec	psi	bar	ins	mm	
DM12VRS	63/64.x2.1	5/16. 25 x 75	36	3 16.5	5 28.7	6 730.	5 1.4	36	7.5	191	980	16	42	20	90	6	3/4.	19	1/2. BSP
Notes:1. Th	e weights sh	own inclu	de a sil	encer	2. The w	eights o	f the bare	tools a	re 3.4lbs (1.5kg)	ighter.								
	СНИС	K SIZE	WE	IGHT	LEN	GTH	ВС	RE	STF	OKE	FRO	Q'CY	AIR	CONS	REC.W	/RKG	AIR H	OSE	HOSE FITTING
model	ins	mm	lbs	kg	ins	mm	ins	mm	ins	mm	bpm	hz	cfm	L/sec	psi	bar	ins	mm	

3/4.

1/2.BSP

(OUTSIDE TRIGGER)

Notes: 1. The weights shown include a silencer 2. The weights of the bare tools are 3.4lbs (1.5kg) lighter.

28.76 730.5

lbs

63/64.x2.15/16. 25 x 75 36.3 16.5