



S1VR- MS3VR - 1UFTVR
U3VR - U5VR - CCVR

S1VR

The S1-VR single head hand held scabblers is the ideal tool for small awkward areas when removing laitence or for concrete repair work. The tool is made to the same high standards for reliable and durable performance as the larger tools in the range with the additional benefit of being vibration reduced to allow longer continuous use by the operator.

model	HEADS		WEIGHT		LENGTH		HEIGHT		WRKING WIDTH		AIR CONS		REC.WRKG		HOSE FITTING
	qty		lbs	kg	ins	mm	ins	mm	ins	mm	cfm	L/sec	psi	bar	
S1VR	1		7.7	3.5	25	635	5	127	0.88	22	5	2.4	90	6	1/2"



MS3VR

MS3-VR Vibration Reduced triple head scabblers is designed for medium duty work in de-scaling, laitence removal and concrete repair. The tools are made to the same high standards for reliable and durable performance as other tools in the range but are vibration reduced to allow the operator longer continuous use.

model	HEADS		WEIGHT		LENGTH		HEIGHT		WRKING WIDTH		AIR CONS		REC.WRKG		HOSE FITTING
	qty		lbs	kg	ins	mm	ins	mm	ins	mm	cfm	L/sec	psi	bar	
MS3VR	3		9.9	4.5	25	635	7	178	3	75	25	12	90	6	1/2"



1UFTVR

For surface preparation of small areas or areas close to walls or between re-bars, the 1UF-TV R is second to none. Its also the ideal tool to compliment the U3-VR or the FB5-VR to scabber edges where larger Machines cant reach. It can remove up to 4 square metres per hour x 4mm deep, to a depth of 50mm. The vibration levels transmitted to the operator by the are typically less than 10% of the levels which are transmitted by the "Standard" 1UF pole scabber.

model	HEADS	WEIGHT		LENGTH		WRKING WIDTH		AIR CONS		REC.WRKG		HOSE FITTING
	qty	lbs	kg	ins	mm	ins	mm	cfm	L/sec	psi	bar	
1UFTVR	1	36	16.5	52	1320	3	75	25	12	90	6	3/4"



U3VR

Vibration Reduced Pneumatic Scabbling Tools are specifically designed for all types of surface work on concrete where it is necessary to carry out surface hammering without in any way damaging the basic concrete.

model	HEADS	WEIGHT		LENGTH		WIDTH		HEIGHT		WRKING WIDTH		AIR CONS		REC.WRKG		HOSE FITTING
	qty	lbs	kg	ins	mm	ins	mm	ins	mm	ins	mm	cfm	L/sec	psi	bar	
U3VR	3	125	57	50	1270	25	635	33	838	5.5/8	143	100	48	90	6	3/4.BSP



U5VR

Vibration Reduced Pneumatic Scabbling Tools are specifically designed for all types of surface work on concrete where it is necessary to carry out surface hammering without in any way damaging the basic concrete.

model	HEADS		WEIGHT		LENGTH		WIDTH		HEIGHT		WRKING WIDTH		AIR CONS		REC.WRKG		HOSE FITTING
	qty		lbs	kg	ins	mm	ins	mm	ins	mm	ins	mm	cfm	L/sec	psi	bar	
U5VR	5		244	111	38	970	22	560	39	990	11. 1/4	286	150		90	6	3/4.BSP



CCMk2VR

The Pneumatic Vibration reduced Crack Chaser is designed to follow cracks on concrete to allow for a clean refilling hole for the new material.

model	HEADS		WEIGHT		LENGTH		WIDTH		HEIGHT		WRKING WIDTH		AIR CONS		REC.WRKG		HOSE FITTING
	qty		lbs	kg	ins	mm	ins	mm	ins	mm	ins	mm	cfm	L/sec	psi	bar	
CCVR	1		137	62	58	1450	20	500	35	865	7/8	22	36	17	90	6	3/4. BSP



VR SCABBLERS

COMPARISON SHEET

VR SCABBLERS

HEADS		WEIGHT		LENGTH		HEIGHT		WRKING WIDTH		AIR CONS		REC.WRKG		HOSE FITTING
model	qty	lbs	kg	ins	mm	ins	mm	ins	mm	cfm	L/sec	psi	bar	
S1VR	1	7.7	3.5	25	635	5	127	0.88	22	5	2.4	90	6	1/2"



S1VR

HEADS		WEIGHT		LENGTH		HEIGHT		WRKING WIDTH		AIR CONS		REC.WRKG		HOSE FITTING
model	qty	lbs	kg	ins	mm	ins	mm	ins	mm	cfm	L/sec	psi	bar	
MS3VR	3	9.9	4.5	25	635	7	178	3	75	25	12	90	6	1/2"



MS3VR

HEADS		WEIGHT		LENGTH		WRKING WIDTH		AIR CONS		REC.WRKG		HOSE FITTING
model	qty	lbs	kg	ins	mm	ins	mm	cfm	L/sec	psi	bar	
1UFTVR	1	36	16.5	52	1320	3	75	25	12	90	6	3/4"



1UFTVR

HEADS		WEIGHT		LENGTH		WIDTH		HEIGHT		WRKING WIDTH		AIR CONS		REC.WRKG		HOSE FITTING
model	qty	lbs	kg	ins	mm	ins	mm	ins	mm	ins	mm	cfm	L/sec	psi	bar	
U3VR	3	125	57	50	1270	25	635	33	838	5.5/8	143	100	48	90	6	3/4"



U3VR

HEADS		WEIGHT		LENGTH		WIDTH		HEIGHT		WRKING WIDTH		AIR CONS		REC.WRKG		HOSE FITTING
model	qty	lbs	kg	ins	mm	ins	mm	ins	mm	ins	mm	cfm	L/sec	psi	bar	
U5VR	5	244	111	38	970	22	560	39	990	11. 1/4	286	150	-	90	6	3/4"



U5VR

HEADS		WEIGHT		LENGTH		WIDTH		HEIGHT		WRKING WIDTH		AIR CONS		REC.WRKG		HOSE FITTING
model	qty	lbs	kg	ins	mm	ins	mm	ins	mm	ins	mm	cfm	L/sec	psi	bar	
CCVR	1	137	62	58	1450	20	500	35	865	7/8	22	36	17	90	6	3/4"



CC Mk2 VR