## **ROGRIND** 13.49 E<sup>3</sup> Hybrid Rail Head Profile Grinding Machine

# ONE MACHINE. TWO MODULES.



### THE ADVANTAGES. YOUR BENEFITS.

#### Precisely ground face in a short time

- Faster working due to constantly high grinding power
- High grinding quality and clear view of the grinding area due to
- Patented ROBEL finish-grinding procedure for localised away
  from the operator reworking

#### Intelligent use of energy

- Loss-free energy conversion from electric motor straight
  to grinding spindle
- ROBEL supercap in power pack: Excess energy stored during idling of grindstone released during load peaks
- Other drive versions (battery, power supply) available

#### Smart positioning, smooth grinding

- Easily transport grinding unit and power pack separately
- Effortless operation due to split machine weight of less than 60 kg each
- Comfortable handling of machine due to ergonomic telescopic handles which are individually adjustable

#### Greater work safety, higher efficiency

- Low hand-arm vibration
- Optimum view of the display at an ergonomic angle of the compact, low-vibration electric motor
- Integrated dust and spark protection due to air exhausted
- Work at a safe distance from exhaust gases, heat and engine noise



SPECIFICATION	
Drive	BLDC electric motor
Continuous rating	6.6 kW (ROPOWER 70.03 + ROBATTERY 71.02)
	3.0 kW (ROPOWER 70.02)
Maximum power	7.0 kW (ROPOWER 70.02)
Circumferential speed	50 m/s
Cup wheel diameter	150 mm
Speed	5000 rpm
Roller spacing	1000 mm
Depth feed of grinding spindle	electric
Dimensions (L x W x H)	1950 x 460 x 850 mm
Without telescopic handles (L x W x H)	1750 x 410 x 850 mm
Weight machine	from 56.5 kg
Weight outrigger	from 8.5 kg

#### ACCESSORIES

5029900002Hybrid drive unit with Honda GX 200 four-stroke engine5026930001Discharging box for discharging the supercaps for maintenance work503990003Power supply 400 Volt (incl. shoulder strap)7839900001Battery 2300 Wh7879900001Charger 2300 Wh5016060200Extension cablel (for battery 2300 Wh)8490800002Outrigger, gauge 1435 mm

Other gauges on request.

9002000690 Cup wheel 150 mm, M20 central nut holder



ROGRIND 13.49 - 8499900008 Outrigger - 8490800002



Battery 2300 Wh - 7839900001



400 Volt power supply - 5039900003



ROPOWER 70.02 - 5029900002

