



Panchro/i Classic S35 T2.2 Primes | Basic specification

Specifications	18mm	21mm	25mm	27mm	32mm	40mm
T-Stop range	T2.2 - T22	T2.2 - T22	T2.2 - T22	T2.2 - T22	T2.2 - T22	T2.2 - T22
Angular rotation of iris scale	90°	90°	90°	90°	90°	90°
Min. marked object distance	200 mm	200 mm	200 mm	175 mm	225 mm	350 mm
	8 in	8 in	8 in	7 in	9 in	13 in
Angular rotation to MOD endstop	270°	270°	270°	270°	270°	270°
Length from front of lens to PL lens mount	87 mm	92 mm	92 mm	92 mm	92 mm	118 mm
	3.4 in	3.6 in	3.6 in	3.6 in	3.6 in	4.6 in
Max. front diameter	110 mm	110 mm	110 mm	110 mm	110 mm	110 mm
	4.3 in	4.3 in	4.3 in	4.3 in	4.3 in	4.3 in
Max. diagonal angle of view for S35 format at 30mm image diagonal	81°	73°	62°	58°	50°	42°
Total weight (with PL lens mount)	1.6 kg	1.5 kg	1.5 kg	1.5 kg	1.1 kg	1.4 kg
	3.5 lbs	3.3 lbs	3.3 lbs	3.3 lbs	2.4 lbs	3 lbs
Screw-in filter	M105 x 0.75	M105 x 0.75	M105 x 0.75	M105 x 0.75	M105 x 0.75	M105 x 0.75

Continued on next page →

Maximum format cover	Super35, optimised for coverage of 31.1 mm
Focus scales	Imperial or Metric scales marked from infinity to MOD
Focus drive gear	140 teeth 0.8 metric module
Iris scales	Two opposing linear T-scales - whole and third stops marked
Iris drive gear	134 teeth 0.8 metric module
Mount	PL or LPL



Panchro/i Classic S35 T2.2 Primes | Basic specification

Specifications	50mm	65mm Macro	75mm	100mm	135mm	152mm
T-Stop range	T2.2 - T22	T2.4 - T22	T2.2 - T22	T2.6 - T22	T2.8 - T22	T3.0 - T22
Angular rotation of iris scale	90°	90°	90°	90°	90°	90°
Min. marked object distance	400 mm	325 mm	700 mm	600 mm	850 mm	1,100 mm
	16 in	13 in	2 ft 6 in	2 ft	2 ft 9 in	3 ft 6 in
Angular rotation to MOD endstop	270°	270°	270°	270°	270°	270°
Length from front of lens to PL lens mount	118 mm	199 mm	155 mm	161 mm	168 mm	168 mm
	4.6 in	7.8 in	6.1 in	6.3 in	6.6 in	6.6 in
Max. front diameter	110 mm	110 mm	110 mm	110mm	110 mm	110 mm
	4.3 in	4.3 in	4.3 in	4.3in	4.3 in	4.3 in
Max. diagonal angle of view for S35 format at 30mm image diagonal	33°	27°	22°	16°	13°	12°
Total weight (with PL lens mount)	1.5 kg	2.8 kg	1.8 kg	1.8 kg	2.1 kg	2.1 kg
	3.3 lbs	6.1 lbs	3.9 lbs	3.9 lbs	4.6 lbs	4.6 lbs
Screw-in filter	M105 x 0.75	M105 x 0.75	M105 x 0.75	M105 x 0.75	M105 x 0.75	M105 x 0.75

Maximum format cover	Super35, optimised for coverage of 31.1 mm
Focus scales	Imperial or Metric scales marked from infinity to MOD
Focus drive gear	140 teeth 0.8 metric module
Iris scales	Two opposing linear T-scales - whole and third stops marked
Iris drive gear	134 teeth 0.8 metric module
Mount	PL or LPL