

**Folded dimensions:**

Length: 0,82 m

Width: 0,56 m

Height: 0,42 m

Weight: 22,65 kg

MALÅ Easy Locator Pro (HDR)

MALÅ Easy Locator Pro is a cost-effective, end-to-end, solution for utility detection and mapping. It is the first Easy Locator being able to export 32 bit HDR data to stand-alone software and the solution comes bundled with both MALÅ ObjectMapper and GPS Mapper software. The Easy Locator Pro Controller uses a single navigator button and the well-known, easy-to-use Easy Locator user interface. The solution has built-in DGPS (SBAS) but supports also stand-alone, external, high precision GPS systems. The solution supports various project types, such as 2D projects, 3D grid projects and ObjectMapper projects. Call us for more information.

Head Office

MALÅ Geoscience AB
Skolgatan 11, S-93070 MALÅ, Sweden
Phone: +46 953 345 50 Fax: +46 953 34567
E-mail: sales@malags.com

Sales Offices

USA Ph.: +1 843 852 5021, Fax: +1 843 284 0684; sales.usa@malags.com
Malaysia Ph.: +60 (0)3 6250 7351, Fax: +60 (0)3 6250 2072; sales@malags.com
China Ph.: +86 108 225 0728, Fax: +86 108 225 0815; sales@malags.com
Australia Ph.: +61 438 278 902, Fax: +61 2 9908 1484; sales@malags.com



MALÅ Easy Locator Pro Controller

| | |
|-------------------------|--|
| Processor: | 1.6GHz Intel Atom |
| Display: | 1024 x 768 |
| OS: | Linux |
| Memory: | 8-32 Gb compact Flash memory |
| Data output resolution: | 32 bit |
| Communication: | Ethernet, USB3.0, RS232 (serial) |
| Built-in GPS: | Integrated support via built-in GPS, or external GPS via USB/serial port (NMEA 0183 protocol). |
| Power supply: | Any external 10-15V DC source. |
| Charger: | Internal bat. source can also be charged from any external 12 - 15V DC source. |
| Power consumption: | 1.3 – 2.0 A |
| Operating time: | 8 – 14 h (depending on number of external batteries) |
| Dimensions: | 430 x 360 x 180, including handles |
| Weight: | 2.5 kg |
| Operating temp: | -20° to +50°C or 0° to 120°F |
| Environmental: | IP65 |



MALÅ Easy Locator Pro HDR

| | |
|------------------------------------|--|
| Technology: | MALÅ Semi-Real-Time ^{pat pending} |
| Antenna center freq.: | 450Mhz |
| SNR: | > 101dB |
| Significant/useful number of bits: | > 16 bit |
| Scans/second: | > 770, time window 300ns |
| Survey speed: | 275 [km/h] point distance 10cm |
| Time window: | 300ns |
| Operating time: | 5 h |
| Bandwidth: | >120%, fractional, -10dB |
| Positioning: | Inbuilt DGPS (SBAS, +/- 1.5m), external GPS, wheel encoder |
| Power supply: | Interchangeable 12V Li-Ion batt. or ext. 12V DC source |
| Power consumption: | 1.3 A |
| Acq. Mode: | Wheel, time or manual |
| Dimensions: | 430 x 360 x 180 mm |
| Weight: | 5.5 kg |
| Operating temp: | -20° to +50°C or 0° to 120°F |
| Environmental: | IP65 |

Alternative to ProCart:

MALÅ Rough Terrain Cart (RTC)

| | |
|---------|---|
| Length: | 1.17 m including handle, 0.94 m without |
| Height: | 1.11 m including handle, 0.41 m without |
| Width: | 0.71 m |
| Weight: | 25 kg |



Head Office

MALÅ Geoscience AB
Skolgatan 11, S-93070 MALÅ, Sweden
Phone: +46 953 345 50 Fax: +46 953 34567
E-mail: sales@malags.com

Sales Offices

USA Ph.: +1 843 852 5021, Fax: +1 843 284 0684; sales.usa@malags.com
Malaysia Ph.: +60 (0)3 6250 7351, Fax: +60 (0)3 6250 2072; sales@malags.com
China Ph.: +86 108 225 0728, Fax: +86 108 225 0815; sales@malags.com
Australia Ph.: +61 438 278 902, Fax: +61 2 9908 1484; sales@malags.com