



S1 - MSG3 - 1UF - LPS

U3 - U5 - NG10

# S1

The S1 single head hand held scabblers is the ideal tool for small awkward areas when removing laitence or for concrete repair work. The tool incorporates a special shaped handle for operator comfort and is made to the same high standards for reliable and durable performance as the larger tools in the range.

model	HEADS	WEIGHT		LENGTH		WIDTH		HEIGHT		WRKING WIDTH		AIR CONS		REC.WRKG		HOSE FITTING
		lbs	kg	ins	mm	ins	mm	ins	mm	ins	mm	cfm	L/sec	psi	bar	
<b>S1</b>	<b>1</b>	<b>6</b>	<b>2.75</b>	<b>21</b>	<b>533</b>	<b>2</b>	<b>50</b>	<b>5</b>	<b>127</b>	<b>7/8</b>	<b>22</b>	<b>5</b>	<b>2.4</b>	<b>90</b>	<b>6</b>	<b>1/2.BSP</b>



# MSG3/P3

The MSG3 triple head, hand held scabblers are designed for medium duty work in de-scaling, laitence removal and concrete repair. The tools are made to the same high standards for reliable and durable performance as the larger tools in the range.

model	HEADS	WEIGHT		LENGTH		WIDTH		HEIGHT		WRKING WIDTH		AIR CONS		REC.WRKG		HOSE FITTING
		lbs	kg	ins	mm	ins	mm	ins	mm	ins	mm	cfm	L/sec	psi	bar	
MSG/P3	3	11	5	21	533	4.68	117	7	178	7/8	22	5	4.8	90	6	1/2.BSP



# 1UF

The Macdonald 1UF is a single unit hand operated pole Scabblers with the same power as a single unit of the heavy multitool Scabblers. It is designed for use in awkward corners, edges where walls and floor surfaces join, or other small areas where the Multi-tool Scabbler is not practical. Its well balanced with an optional extended side handle, making it easily operated and controlled from an upright position.

model	HEADS		WEIGHT		LENGTH		WIDTH		HEIGHT		WRKING WIDTH		AIR CONS		REC.WRKG		HOSE FITTING
			lbs	kg	ins	mm	ins	mm	ins	mm	ins	mm	cfm	L/sec	psi	bar	
1UF	1		29	13	52	1320	3	75	...	...	2.1/4.	57	25	11.8	90	6	1/2.NPT



# U3

The Macdonald U3 three headed trolley scabblers are specifically designed for surface work on concrete where it is necessary to carry out surface hammering without indamaging the basic concrete.

model	HEADS		WEIGHT		LENGTH		WIDTH		HEIGHT		WRKING WIDTH		AIR CONS		REC.WRKG		HOSE FITTING
			lbs	kg	ins	mm	ins	mm	ins	mm	ins	mm	cfm	L/sec	psi	bar	
U3	3		125	57	50	1270	25	635	33	838	5.5/8	143	100	48	90	6	1" NPT



\*Optional cover at extra cost

# U5

The Macdonald U5 five headed trolley scabblers are specifically designed for surface work on concrete where it is necessary to carry out surface hammering without damaging the basic concrete.

model	HEADS		WEIGHT		LENGTH		WIDTH		HEIGHT		WRKING WIDTH		AIR CONS		REC.WRKG		HOSE FITTING
	qty		lbs	kg	ins	mm	ins	mm	ins	mm	ins	mm	cfm	L/sec	psi	bar	
U5	5		244	111	38	970	22	560	39	990	11. ¼	286	150		90	6	1" NPT



# LPS3/5

The Macdonald LPS Tools can be used to remove tiles, paint, epoxy and bituminous coatings from floors, walls and other flat surfaces. Two sizes are available for comfort. An optional needle holder attachment is available and or, scraping blades up to 12" (300mm) wide.

model	HEADS		WEIGHT		LENGTH		WIDTH		HEIGHT		WRKING WIDTH		AIR CONS		REC.WRKG		HOSE FITTING
	qty		lbs	kg	ins	mm	ins	mm	ins	mm	ins	mm	cfm	L/sec	psi	bar	
LPS3	1		11	5	39	1000	2.25	57	...	...	4	102	10	4.8	90	6	1/2"NPT
LPS5	1		12	6	55	1400	2.25	57	...	...	4	102	10	4.8	90	6	



# NG10

*The Macdonald NG10 Needle gun is the ideal tool for the removal of paint, rust and accumulated scale from a wide variety of surfaces. It can be used in many different applications such as stone cleaning and restoring, welding, tank cleaning and removal of corrosion caused by sea water on shipping etc.*

model	HEADS		WEIGHT		LENGTH		WIDTH		HEIGHT		WRKING WIDTH		AIR CONS		REC.WRKG		HOSE FITTING
			lbs	kg	ins	mm	ins	mm	ins	mm	ins	mm	cfm	L/sec	psi	bar	
NG10	28		10	4.5	12	305	2.25	55	...	....	2	50	10	4.8	90	6	1/4" BSP



STANDARD SCABBLERS

# STANDARD SCABBLERS

## COMPARISON SHEET

STANDARD SCABBLERS

model	HEADS	WEIGHT		LENGTH		WIDTH		HEIGHT		WRKING WIDTH		AIR CONS		REC.WRKG		HOSE FITTING
		lbs	kg	ins	mm	ins	mm	ins	mm	ins	mm	cfm	L/sec	psi	bar	
S1	1	6	2.75	21	533	2	50	5	127	7/8	22	5	2.4	90	6	1/2.BSP



S1

model	HEADS	WEIGHT		LENGTH		WIDTH		HEIGHT		WRKING WIDTH		AIR CONS		REC.WRKG		HOSE FITTING
		lbs	kg	ins	mm	ins	mm	ins	mm	ins	mm	cfm	L/sec	psi	bar	
MSG/P3	3	11	5	21	533	4.68	117	7	178	7/8	22	5	4.8	90	6	1/2.BSP



MSG3

model	HEADS	WEIGHT		LENGTH		WIDTH		HEIGHT		WRKING WIDTH		AIR CONS		REC.WRKG		HOSE FITTING
		lbs	kg	ins	mm	ins	mm	ins	mm	ins	mm	cfm	L/sec	psi	bar	
1UF	1	29	13	52	1320	3	75	...	...	2.1/4.	57	25	11.8	90	6	1/2.NPT



1UF

model	HEADS	WEIGHT		LENGTH		WIDTH		HEIGHT		WRKING WIDTH		AIR CONS		REC.WRKG		HOSE FITTING
		lbs	kg	ins	mm	ins	mm	ins	mm	ins	mm	cfm	L/sec	psi	bar	
LPS3	1	11	5	39	1000	2.25	57	...	...	4	102	10	4.8	90	6	1/2BSP
LPS5	1	12	6	55	1400	2.25	57	...	...	4	102	10	4.8	90	6	



LPS

model	HEADS	WEIGHT		LENGTH		WIDTH		HEIGHT		WRKING WIDTH		AIR CONS		REC.WRKG		HOSE FITTING
		lbs	kg	ins	mm	ins	mm	ins	mm	ins	mm	cfm	L/sec	psi	bar	
U3VR	3	125	57	50	1270	25	635	33	838	5.5/8	143	100	48	90	6	3/4" BSP



U3

model	HEADS	WEIGHT		LENGTH		WIDTH		HEIGHT		WRKING WIDTH		AIR CONS		REC.WRKG		HOSE FITTING
		lbs	kg	ins	mm	ins	mm	ins	mm	ins	mm	cfm	L/sec	psi	bar	
U5	5	244	111	38	970	22	560	39	990	11. 1/4	286	150		90	6	3/4.BSP



U5

model	HEADS	WEIGHT		LENGTH		WIDTH		HEIGHT		WRKING WIDTH		AIR CONS		REC.WRKG		HOSE FITTING
		lbs	kg	ins	mm	ins	mm	ins	mm	ins	mm	cfm	L/sec	psi	bar	
NG10	28	10	4.5	12	305	2.25	55	...	...	2	50	10	4.8	90	6	1/4" BSP



NG10