

Compressor Information - C38 (GS - Generator Optional)

Model	C38 (GS - Generator Optional)
Series	C Series
Description	Portable Compressors (C Series - 3.5 to 7.6 m ³ /min)
Gas Compressed	Air
Output Free Air Delivery at Rated Pressure (m ³ per min)	3.8
Minimum Operating Pressure (Bar g)	5
Max or Rated Operating Pressure (Bar g)	7 to 8
Maximum Operating Pressure (Bar g)	8
Motor Output (kW)	35.5
Noise Level (db)	98
Length (mm)	3065
Width (mm)	1490
Height (mm)	1327
Compressed Air Outlets (Inches)	2 x 3/4"
Off Load Speed (rpm)	1700
Full Load Speed (rpm)	2800
Oil capacity (l)	9
Weight: Straight towbar, braked (kg)	748
Weight: Adjustable towbar, braked (kg)	808 (875/892 for G/GS version)
Fuel Tank Capacity (l)	60
Canopy Length (mm)	1775
Engine Type	Cummins A 2300
Cooling System	water cooled - 7.5(l)

At Rated Operating Pressure (Bar g):	7
Output Free Air Delivery (m ³ /min):	3.8



Additional Information

The latest CompAir Range of Portable Compressor incorporate the very latest technological advances and manufacturing processes to provide users with a portable supply of economic and reliable compressed air.

Dimensions shown are braked with straight towbar - please see PDF spec sheet for more information and options

Power sound level (dB(A)) acc. to 2000/14/EC 2) (Legal limiting values of EC directive from 01.2006)

Please see pdf brochure (left) for Electrical generator information

*images may show a similar model to that stated - please contact [your sales and service provider](#) for pricing and further information. Inlet pressure = 1 bar unless otherwise stated