

**CONCRETE  
MIXERS****FEATURES**

- Three model sizes, 150-100 litre, 200-150 litre and 280-200 litre.
- Totally enclosed "safety lube drive".
- Unbreakable steel mixing drum.
- Full lift engine canopy.
- Heavy duty gear mechanism.
- Drive to drum by stretchless "V" belt.
- Solid rubber wheels for longer life.
- Machine cut crownwheel and bevel pinion made of special toughened heat treated steel.



# TEREX

| CONCRETE MIXERS             |                      |                   |                   |
|-----------------------------|----------------------|-------------------|-------------------|
|                             | CT                   | LS                | RG                |
| Engine                      | Hatz 1B20            | Hatz 1B20         | Lister LV1-09     |
| Power                       | 1.5 kW @ 1500 rpm    | 1.5 kW @ 1500 rpm | 1.5 kW @ 1500 rpm |
| Capacity - Unmixed (litres) | 150                  | 200               | 280               |
| Capacity - Mixed (litres)   | 100                  | 150               | 200               |
| Loading Height (mm)         | 1041                 | 1085              | 1110              |
| Drum Speed (rpm)            | 20                   | 21                | 20                |
| Drum Opening (mm)           | 483                  | 533               | 546               |
| Discharge Height (mm)       | 660                  | 638               | 580               |
| Length less draw bar (mm)   | 1727                 | 1910              | 2040              |
| Width (mm)                  | 813                  | 975               | 1035              |
| Height - Drum Vertical (mm) | 1651                 | 1710              | 1835              |
| Height - Drum Inverted (mm) | 1524                 | 1609              | 1640              |
| Frame Construction          | Welded Steel Channel |                   |                   |
| Tyres                       | Rubber Cushion       |                   |                   |
| Length (m)                  | 1.78                 | 1.91              | 2.08              |
| Width (m)                   | 0.83                 | 0.98              | 1.18              |
| Height (m)                  | 1.56                 | 1.61              | 1.65              |
| Volume (m <sup>3</sup> )    | 2.3                  | 3.01              | 4.05              |
| Maximum Weight (kg)         | 404                  | 437               | 631               |

TEREX Compact

Central Boulevard, Prologis Park,

Coventry, England, CV6 4BX

Tel: +44(0)24 7633 9400 Fax: +44(0)24 7633 9500

Email: [enquiries@terexce.com](mailto:enquiries@terexce.com)

[www.terexce.com](http://www.terexce.com)

Dealer

[www.terex.com](http://www.terex.com)

For further information, please contact your local distributor or the TEREX sales office listed. TEREX pursues a policy of continuous development for its products. Product specifications are subject to change without notice or obligation. The photographs and drawings in this brochure are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. Prices and specifications subject to change without notice. The only warranty applicable is the standard written warranty applicable to the particular product and sale. TEREX makes no other warranties, whether expressed or implied.

Copyright ©04.2006

MG 0406-EN