

## Combi Drill LXT®

### DHP453

18V • 42 Nm • 0 – 1 300 min<sup>-1</sup>

**Combi drill with hammer action for demanding amateur builders**

For screwdriving and drilling with or without hammer action, two power settings. Max. torque of 42 / 27 Nm. Suitable for light professional use or demanding amateur use



**LXT**

#### Technical specifications

Nominal Battery Voltage	18 V
Voltage LXT	✓
No load speed	0 - 400 / 1300 min <sup>-1</sup>
Max. fastening torque Hard/Soft	42 / 27 Nm
Torque setting	16
Impacts per Minute (IPM)	0 - 6000 / 19500 min <sup>-1</sup>
Max. Drilling Diameter in Wood	36 mm
Max. Drilling Diameter in Masonry	13 mm
Max. Drilling Diameter in Steel	13 mm
Drill Chuck Capacity	1,5 - 13 mm
Sound Power Level (L <sub>WA</sub> )	94 dB(A)
Sound Pressure Level (L <sub>pA</sub> )	83 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes), Drilling	≤ 2,5 m/s <sup>2</sup>
Vibration Level (3 axes), Impact Drilling	10,0 m/s <sup>2</sup>

#### User benefits

- The rubber coating on the handle ensures a firm working grip
- Battery protection circuit protects against overloading, over-discharging and over-heating

Link to product - [www.makita.com](http://www.makita.com)



# Related products

## Optional AC

**158777-2**

Plastic carrying case



**196306-3**

Keyless chuck 13 mm, 1/2" - 20UNF



**450128-8**

Battery cover, LXT®, 14,4 – 18V



**BL1820B**

Battery LXT® 2,0 Ah



**BL1830B**

Battery LXT® 3,0 Ah



**BL1840B**

Battery LXT® 4,0 Ah



**BL1850B**

Battery LXT® 5,0 Ah



**BL1860B**

Battery LXT® 6,0 Ah



**D-42204**

COUNTERSINK 6PC SET



**D-47139**

Holesaw Set



**D-47363**

Forstner Drill Bit Set, 5 pcs



**E-08698**

Flat bit set 8 pcs



## Other

[User manual](#)

[Parts drawing](#)