


PRODUCT INFORMATION

G100RS | Rental Set



DIESEL GENERATOR

STAGE IIIA

ELECTRICAL

Frequency (Hz)	Phases	Voltage (V)	Prime		Standby		MCB Rating (A)	Minimum ATP Rating (A)	Rated Speed (RPM)
			kVA	kW	kVA	kW			
50	3	400/230V	100	80	110	88	200	200	1500
60	3	480/277V	N/A	N/A	N/A	N/A	N/A	N/A	1800

POWER FACTOR

3 Phase	0.8
1 Phase	1

MAXIMUM LOAD IMPACT*

kVA	60
kW	48

*With 20% voltage and 10% frequency deviation @ 50Hz, 400V

ALL RATINGS ARE TO STANDARD REFERENCE CONDITIONS ISO 8528

Prime: This rating is for the supply of continuous electrical power, at variable load, in lieu of commercially purchase power. There is no limitation on the annual hours of operation and 10% over load power can be supplied for 1 hour in 12.

Standby: Standby Power (ESP) is the maximum output available, for up to 500 hours per year, where the average load (variable) does not exceed 70% of the standby power rating. No overload is available.

Stage IIIA models are only emissions compliant at 50Hz Prime Power in accordance with 97-68EC.

GI00RS | Rental Set



**GENERATORS
IRELAND**

CANOPY

Lockable Maintenance Access Doors	•
Control Panel Viewing Window	•
Oversized Fork Pockets	•
Welded Single Lift Point	•
Bunding	•
Certified 4 Point Lift	•
High Density Fire Retardant Foam	•
Yellow Paint	Δ
White Paint	•
Heavy Duty Rental Base	•
Drag Bar	Δ
Galvanised Steel Canopy	•
Standard: • Not Available: x Optional: Δ	

ALTERNATOR ECP34-2S4 A

Poles	4
Winding Connections	Star
Insulation	Class H
Enclosure	IP23
Exciter System	Self-regulating brushless
Voltage Regulator	AVR
Steady State Voltage Regulation	+/- 1%
Bearing	Single bearing sealed
Coupling	Flexible disc
Cooling	Direct drive centrifugal blower fan
Coating	Total Protection +

STARTING SYSTEM

Starter Motor	kW	4.20
Battery Capacity	Ah	120
Number of Batteries		1
Auxiliary Voltage	V	12

ENGINE

1500 RPM		
Net Output Rating (PRP)	kW	88
Net Output Rating (Standby)	kW	93
1800 RPM		
Net Output Rating (PRP)	kW	N/A
Net Output Rating (Standby)	kW	N/A
Manufacturer and Model		
		JCB 448 G-TCA 92
Fuel		
		Diesel
Injection		
		Direct
Aspiration		
		Turbo Charged
Cylinders		
		4
Bore and Stroke	mm	103 x 135
Displacement	L	4.77
Cooling		
		Water
Engine Oil Specification		
		API CH4
Compression Ratio		
		18 : 1
Engine Oil Capacity	L	15.00
Coolant Capacity	L	16.00
Governor		
		Mechanical
Air Filter		
		Two stage Paper Element
Engine Oil Consumption	100% Load	0.1% of fuel consumed

FUEL SYSTEM

Diesel Specification		EN590
Standard Capacity Fuel Tank	L	280
Extended Capacity Fuel Tank(Optional)	L	560

G100RS | Rental Set



**GENERATORS
IRELAND**

FUEL CONSUMPTION

Load	Unit	Frequency	Consumption
100% Load Prime	L/h	50Hz	23.6
75% Load Prime	L/h		17.8
50% Load Prime	L/h		12.50
100% Load Standby	L/h		25.60
100% Load Prime	L/h	60Hz	N/A
75% Load Prime	L/h		N/A
50% Load Prime	L/h		N/A
100% Load Standby	L/h		N/A

EXHAUST SYSTEM

Maximum Temperature 100% Standby	°C	50Hz	548.00
Exhaust Gas Flow 100% Standby	m ³ /min		18.86
Maximum Allowed Back Pressure	kPa		10.00
Exhaust Discharge Size	mm	100	

AIR SYSTEM

Intake Air Flow 100% Standby	m ³ /h	50Hz	402.00
Total Cooling Air Flow 100% Standby	m ³ /s		3.30

SOUND PRESSURE

LpA (7m)	50Hz	dB(A)	67
----------	------	-------	----

MECHANICAL FEATURES

Cooling Pack	•
Air Filter	•
Mechanical Governor	•
Low Oil Pressure Switch	•
Coolant Temperature Sender	•
Oil Temperature Sender	•
Radiator Guards	•
Hot Component Guards	•
Manual Oil Drain Pump (Canopy)	Δ
Water Jacket Heater	Δ
Pre-Filter with Separator	•
Fuel Level Sender	•
Internal Fuel Fill (Belly Tank)	•
3 Way Fuel Valve	•
Residential Silencer	•
Air Shut-Off Valve	Δ
Electronic Governor	Δ
Spark Arrestor	Δ

Standard: • Not Available: x Optional: Δ

GI00RS | Rental Set



**GENERATORS
IRELAND**

ELECTRICAL FEATURES

AVR DSR	●
AVR DER	x
Winding Protection Standard	x
Winding Protection Standard +	x
Winding Protection Grey	x
Winding Protection Total	x
Winding Protection Total +	●
MAUX	●
PMG	Δ
Anti-Condensation Heater	Δ
3 Pole Moulded Case Circuit Breaker	x
4 Pole Moulded Case Circuit Breaker	●
Earth Leakage Protection (Switchable)	●
Preparation for Earth Spike	●
Optional Voltages	Δ
Emergency Stop Button (Control Panel)	●
External Emergency Stop Button	●
AGM Battery	Δ
Socket Panel (1 x 32A – 3ph, 3 x 32A – 1 ph) IP44	x
Socket Panel (1 x 63A – 3ph, 3 x 32A – 1 ph) IP44	x
Socket Panel (1 x 63A – 3ph, 2 x 32A – 3ph, 3 x 32A – 1 ph) IP44 (1 x 125A – 3ph) IP67	Δ
Bund Alarm / Shut down	Δ
Remote Display	x
50Hz / 60Hz Switch	Δ
Standard: ● Not Available: x Optional: Δ	

BATTERY FEATURES

Battery Isolator	●
Battery Type	SEALED LEAD ACID
Battery Size (Ah)	120
Number of Batteries	1
Battery Charger	Δ

JCB COMMUNICATION AND CONTROL

7320 MKII	●
8610 MKII (Synchronisation)	Δ
8620 (Synchronisation)	Δ
LiveLink for Power (MKII Panel Only)	●
Standard: ● Not Available: x Optional: Δ	

WEIGHT AND DIMENSIONS

Length	mm	3334
Width	mm	1200
Height	mm	1912
Shipping Volume (sea ready)	m ³	7.70
Weight*	Kg	2120

*Standard build with all fluids except fuel

CE PACK

EMC Certification	●
Hot Guards	●
Belt Guards	●
Sound Power Decal	●
EU Declaration for Engine Emissions	●
Complete Machine Declaration of Conformity	●
Standard: ● Not Available: x Optional: Δ	

REFERENCE STANDARDS

JCB Generators are CE certified and conform to the following Directives (subject to a country requiring such standard):

- EN 12100, EN13857, EN60204
 - 2006/42/CE Machinery safety
 - 2006/95/EC Low voltage
 - 2004/108/CE Electromagnetic compatibility
 - 2000/14/EC Sound Power Level (amended by 2005/88/EC)
 - 97/68/EC Emissions(amended by 2002/88/EC & 2004/26/EC)
 - Power according to ISO 8528 and ISO 3046
 - Ambient reference conditions 1000mbar, 25°C, 30% relative humidity ISO3046
- Information based on standard specification equipment unless otherwise stated.