

TS 410 - Compact and robust 3.2-kW cut-off saw (300mm/12" cutting wheel)



Compact and robust, the new STIHL TS 410. Long-life filter system with cyclone pre-separation makes on site maintenance unnecessary. Extremely low vibration levels (3.9m/s²). High performance engine with stratified charge system. Compact design and optimised balance for excellent cutting and guide characteristics. For use with 300mm cutting wheel. ElastoStart, primer pump and decompression valve. Bayonet filler cap for tool free opening. Can be hand held or used with the FW 20 cart.

Technical data

Displacement	66.7 cm ³
Diameter of abrasive wheel	300 mm
Vibration levels left/right	3.9/3.9 m/s ²
Maximum cutting depth	100 mm
Weight ¹⁾	9.4 kg
Power output	3.2/4.4 kW/bhp
Sound power level ²⁾	109.0 dB(A)
Sound pressure level ²⁾	98.0 dB(A)

¹⁾ without abrasive wheel

²⁾ Power factor according to DIR2006/42/EC=2.5(dB(A))

Models available

TS 410

[Add to product list](#)

[View product list \(0\)](#) 

Standard features

- Reduced-emission engine technology
- Long life air filter system (cyclone)
- Anti-vibration system
- ElastoStart
- Manual fuel pump (Purger)
- Compensator
- Decompression valve
- Ergonomic grip position

Additional features

- Cut-off saw cart

Variations

- With 350mm cutting wheel

[Click here to find your local STIHL Approved Dealer](#)

The version(s) available in each country may differ from the above range and specifications; specific details may be subject to change without notice. Please ask your local STIHL Approved Dealer for further information