

## Circular Saw LXT®

### BSS611

18V • 3 700 min- • 165 mm

18V LXT Cordless saw that cuts at high rotational speed of 3,700 RPM . Saw's grip provides more control and comfort. Easy to adjust cutting depth with safety cover with calibration line. Aluminum base provides high quality and toughness for better work results. Bevel cuts from 0° to 45° for the most common cutting applications



#### Technical specifications

Nominal Battery Voltage	18 V
Voltage LXT	✓
Max. Cutting Depth at 90°	57 mm
Max. Cutting Depth at 45°	40 mm
Max. Cutting Depth at 50°	36 mm
Max. Bevel Range (Left)	0 / 50 °
No load speed	3700 min <sup>-1</sup>
Noise Uncertainty (K Factor)	3 dB(A)
Tool weight with battery (EPTA)	2,9 - 3,2 kg
Product Dimensions (L x W x H):	347 x 202 x 228 mm
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Max Output Power	360 W
Capacity 45°	40 mm
Blade Diameter	165 mm
Bore Size (Arbor Diameter)	20 mm
Product net weight	2,5 kg

#### User benefits

- Rubberised soft grip handle provides increased comfort on the job
- Lightweight and compact design for easy handling

Link to product - [www.makita.com](http://www.makita.com)



# Related products

## ■ Optional AC

164095-8  
Parallel Guide



783203-8  
Hex Wrench 5 Mm



---

## ■ Other

User manual

Parts drawing