

Product Applications	Target Customers	Range USP
<ul style="list-style-type: none"> • Suitable for most Industrial and Commercial Applications • Dockyards and ship building • Power stations • Factories • Construction • Forges & Mining • Processing plants • Military Installations • Warehouses • Marquees & Events • Exhibition halls • Hospitals • Temporary Buildings 	<ul style="list-style-type: none"> • Hire Companies • Construction Firms • Procurement Managers • Facility Management • Wholesalers & Resellers • Large Industrial Units 	<ul style="list-style-type: none"> • The industry standard Fireflo range of portable infra red space heaters and fan heaters is a fixture in many of the worlds leading hire fleets and industrial supply catalogues. Designed using the very latest in heating and airflow technology the range includes infra red heaters, standard fan heaters and high volume machines suitable for ducting through multiple outlets or long distances. All built to withstand industrial use using the same high spec of materials and production methods this extensive range has something to suit every application and is an ideal safe, clean, fume free alternative to gas and diesel.



Product Image	Product Specs	Product USP
<p>FF42</p>	<p>Airflow Rate 4000m³/hr Nominal Output 42kW Supply 400v 50hz Plug Size 63A Sound (3m) 73dB(A) Spigot 500mm Mobility Portable Thermostat Standard Remote Thermostat Standard Max Ducting 10m Dimensions HxWxD (mm) 1000x700x1100 Weight 130kG Overtemp protection Yes Phase protection Yes 24v Control Circuit</p>	<p>The most powerful 63A heater available. Designed and built for industrial use the FF42 features variable heat output, 24V control circuit for safety, remote thermostat socket, spigot, over temperature protection and an auto run on as standard. The FF42 is fitted with a powerful forward curved impeller that can deliver heat along 10m of ducting</p>

Off-Fan-21kW-42kW settings



Thermostat Thermostat coupler



Lifting eyes for maximum portability



Remote thermostat (optional extra)



10m 500mm duct (optional extra)