



PCEL 320X



A lightweight professional compaction plate with low Hand Arm Vibration and high performance compaction. Specifically designed to offer excellent portability and manoeuvrability on site. The ideal "Patching" Plate Compactor.

- Low Hand Arm Vibration design for longer, safe usage times.
- High performance 11kN vibration unit for excellent forward travel speed.
- Sealed oil-filled vibrator with top quality bearings for reliability and durability.
- Front and rear manual handling points for an easy two-man lift.
- Removable and ultra low folding operator's handle for ease of transportation and storage.
- 8mm thick long life base plate for optimum compaction and reliability.
- Engineered to be robust and durable for rental and heavy contractor use.



8mm thick long life base plate



Ideal patching plate compactor



Removable fold down handle



320mm wide base plate



PCEL 320X



Honda 3Hp Engine as standard



Ideal Asphalt plate compactor



11kN vibration unit



Compact design for confined areas



Low HAV mountings

Model	Part Number	Engine Power (Hp) - (kW)	Plate Size (mm)	Static Pressure (kg/m ²)	Centrifugal Force (kN)	Travel Speed (m/min)	Vibration level* (m/sec ²)	Weight (kg)	Price (£)
PCEL 320X Honda Petrol	ELX3201	3 - 2.2	320x364	425	11	22	4.42*	49	788

* Vibration levels tested to BS5349 using EN 500-4



PCLX 320-400

A midweight professional compaction plate with low Hand Arm Vibration and high performance compaction. The PCLX is designed for contracting and rental use.

- Low Hand Arm Vibration design for longer, safe usage times.
- High performance 13kN vibration unit for maximum compaction and good forward travel speed.
- Sealed oil filled vibrator with top quality bearings for reliability and durability.
- Manual handling points for an easy lift.
- Lifting eye protects engine and ensures balanced machine lifting.
- Easy to operate and control, the base plate does not dig in when dragged backwards or turned.
- Engineered to be robust and durable for rental and heavy contractor use.



Heavy duty manual handling point



Extra thick cast base plate



Honda 3Hp engine as standard

PCLX 320-400



PCLX complete with water kit option



PCLX complete with wheel kit option

Model	Part Number	Engine Power (Hp) - (kW)	Plate Size (mm)	Static Pressure (kg/m ²)	Centrifugal Force (kN)	Travel Speed (m/min)	Vibration level** (m/sec ²)	Weight (kg)	Price (£)
PCLX 320 Honda Petrol	LC3201	3 - 2.2	320x417	460	13	21.2	3.25**	61.5	831
PCLX 400 Honda Petrol	LC4001	3 - 2.2	400x417	384	13	21.2	3.68**	64	874

Options

Description	Part Number	Price (£)
Block paving pad PCLX 320	OPP/01.D/IO	59
Block paving pad PCLX 400	OPP/02.D/IO	75
PCLX 320 Water Spray System	OPP/03.D/IO	124
PCLX 400 Water Spray System	OPP/04.D/IO	124
*PCLX Detachable wheel Kit	OPP/00.D/IO	68

*Compatible with models serial no: 050570 and beyond only

**OPERC independent testing/Vibration levels tested to BS5349 using EN 500-4