

Manufacturer	SkyJack
Machine	MEWP – Diesel Scissor
Model	SJ6826RT Compact RT

PERFORMANCE		Unit
Maximum Platform Height	7.9	m
Working Height	9.8	m
Lift Time	36	secs
Lower Time	36	secs
Platform Capacity standard	567	kg

DIMENSIONS		Unit
Stowed Height		m
Stowed Height with rails up	2.37	m
Stowed Height with rails lowered	1.61	m
Minimum Transport Length	2.72	m
Minimum Transport Height		m
Overall Width	1.73	m
Wheelbase	2.04	m
Ground Clearance	0.203	m
Ground Clearance (pothole guards deployed)		m
Platform Width	1.42	m
Platform Length	2.44	m
Standard Platform Extension – Side 1	1.52	m
Standard Platform Extension – Side 2		m
Optional Platform Extension – Side 1		m
Optional Platform Extension – Side 2		m
Stabiliser Levelling – Fore & Aft		°
Stabiliser Levelling – Side to Side		°
Platform Height (Lowered)	1.23	m
Maximum Drive Height	9.8	m

POWER		Unit
Power Source	Petrol / LPG	
Optional Power Source 1	Diesel	
Optional Power Source 2		
Engine Make		
Engine Model		
Engine Power		kW
Engine Fuel	Petrol / LPG	
Optional Engine Make		
Optional Engine Model		
Optional Engine Power		kW
Optional Engine Fuel	Diesel	
Optional Engine Make 2		
Optional Engine Model 2		
Optional Engine Power 2		kW
Optional Engine Fuel 2		
Drive Motors – Type		
Hydraulic Pump Type		
Hydraulic Pump Motor Type		
Batteries		



TRAVEL		Unit
Tyre Size	12 x 26	
Tyre Type	Foam Fill	
Inside Turn Radius	1.52	m
Outside Turn Radius	3.96	m
Turn Radius with Extended Axle		m
Drive Speed (Elevated)	0.6	kph
Gradeability – 2WD		%
Gradeability – 4WD	50	%
Drive Speed – 2WD		kph
Drive Speed – 4WD		kph

WEIGHTS & CAPACITIES		Unit
Fuel Tank Capacity		ltr
Hydraulic Tank Capacity		ltr
Operating Weight	2,926	kg