

4394RT

Diesel Powered Scissor Lifts RT Series

Features

- Choice of single or dual deck extensions for increased workspace
- Optional auto-leveling jacks for quicker set up
- Driveable up to maximum platform height for increased productivity

Quick Specs

- Platform Height Elevated – 13.10 m
- Overall Width – 2.39 m
- Platform Capacity – up to 680 kg



4394RT Specifications

* Certain weights and dimensions may vary due to options and to compliance with country standards.

** Ground bearing pressure applies to standard tires.

Power System/Chassis

Axle Oscillation (Optional)	8" / 20 cm
Brakes (4 Wheel - 3394RT & 4394RT)	Spring Applied
Dual Fuel Engine (Water-Cooled - 3394RT & 4394RT)	GM Vortec 3000 MPFI 82 hp / 61 kW
Diesel Engine (Air-Cooled - 3394RT & 4394RT)	Deutz D2011L03 49 hp / 36.5 kW
Fuel Tank Capacity	30 gal. / 113.56 L
Hydraulic Reservoir	40 gal. / 151.42 L

Performance Data

Platform

Capacity	1,500 lb / 680 kg
- Capacity on Extension	500 lb / 227 kg
- Capacity w/Dual Extensions	1,250 lb / 567 kg
Lift/Lower Time	40/43 seconds
Maximum Drive Height	Full Height
Weight* (ANSI/CSA)	15,300 lb / 6,940 kg
Ground Bearing Pressure**	169 psi / 11.83 kg/cm ²
Drive Speed (Lowered - 260MRT)	4 mph / 6.4kmph
Gradeability	45%
Turning Radius - Inside	8' 10.5" / 2.71 m
Turning Radius - Outside	19' 5.5" / 5.93 m
Tire Size	33 x 15.5
Tire Type	Superwide

Dimensions

Platform Height - Elevated	43' / 13.11 m
Platform Height - Lowered	5' 10.4" / 1.79 m
Platform Railing Height	3' 7.5" / 1.1 m
Overall Height (Rails Lowered - 3394RT & 4394RT)	7' 2.4" / 2.19 m
Stowed Height (Rails Folded) - 260MRT	
Platform Dimensions	86 x 150" / 2.18 x 3.81 m
- Platform Extension	4' / 1.22 m
Overall Length	12' 8" / 3.86 m
Overall Width	7' 10" / 2.39 m
Wheelbase	9' 8" / 2.95 m
Ground Clearance	12" / 30 cm

