

PORTABLE AC CHARGER FOR ELECTRIC VEHICLES



The CUBICHARGE:EV has been designed to offer a portable, temporary electric vehicle charging solution in a compact, hard-wearing cube.

By connecting the unit to an available three phase electrical supply, or generator, it provides Mode 3, 7.2kW fast charging for up to 3 EVs.

Complete with carry handles, mounting feet, built-in protective switchgear and LED charging status indicators, the CUBICHARGE:EV is the ideal portable charging solution for use at events, car showrooms, service centres, R&D facilities – in fact, anywhere temporary and portable EV charging is required.

Designed to be compatible with all current PHEVs and EVs.

Product Features

- Mode 3 (IEC 61851-1) fast charging
- 3way, 7.2kW (32A) charging speed
- Type 2 (IEC 62196) charging sockets
- Built-in AC overload & fault current protection
- Built-in DC sensitive protection
- Built-in LED charging status indicator socket halos
- Built-in electrical input coupler
- Carry handles and rubber stabilising feet
- Easy to transport, set up and use
- Manufactured to IP55 British Standard Institute (BSI) specifications
- Corrosion resistant
- UV stabilised
- Fire retardant
- Impact resistant

3 Way
Charging Unit

Branding and
Colour Options
Available

Ideal Temporary
EV Charging
Solution

Impact
Resistant

IP Rated and
UV Stabilised

Flame
Retardant

PORTABLE AC CHARGER FOR ELECTRIC VEHICLES

Specifications

Product Code	EVCC0030
Charging Sockets	3x Type 2 (IEC 62196)
Rated Output	7.2kW
Rated Current	32A
Charge Protocol	Mode 3
Input Voltage	3 Phase 32A 400V
Input Connection	IP67 5-Pin Plug
AC Fault Protection	30mA
DC Fault Protection	6mA
Standby Consumption	Approx 0.3kWh per day
Certifications & Compliances	EV Charging Compliance – EN 61851-1:2001, EN 61851-21:2002, EN 61851-22:2002 Wiring Regulations – BS 7671 EMC Compliance – EN 61000-6-3:2007, EN 61000-6-2:2005 Safety Compliance (LVD) – 2014/35/EU Environmental Protection – Enclosure IP55, Socket IP54, Inlet IP67, Switchgear access window IP65 (BS EN 60529:1992+A2:2013)
Dimensions	400mm x 487.5mm x 455mm (W x H x D)
Outer Shell Material	Polypropylene
Panel Material	3.2mm Aluminium composite
Stabilising Feet Material	Rubber
Operating Temperature	-30°C to +50°C
Standard Body Colour	Black
Standard Panel Colour	Black (Other colours available upon request)

Options and Accessories

- Key switch control charging
- Built-in class 1 MID compliant kWh meter
- Corporate branding (colours, logo badge, etc.)
- EV charging cables (Type 1 to Type 2 or Type 2 to Type 2)

